

Week 9

GUI Lists

This week

- Packages
- ListView
- Opening and closing windows
- Controls
- Change listeners

Packages

Packages

- A package is a collection of related classes.
- Each application or library should be placed in its own package.
- To avoid two programmers using the same package name for their application, we follow a convention:
 - Companies use the reverse of their domain name.
e.g. For domain name **mycompany . com**, use the package name **com . mycompany**
 - Different applications made by the same company are in sub-packages.
e.g. **com . mycompany . calculatorapp** and **com . mycompany . studyapp**

Packages

- Complex applications are further divided into sub-packages.
- e.g. in an MVC application, you may have 3 sub-packages:
 - `com.mycompany.studyapp.model` contains the domain model classes
 - `com.mycompany.studyapp.view` contains the views
 - `com.mycompany.studyapp.controller` contains the controller classes

Package declarations

- Declare a class in a package with a package declaration:

```
package com.mycompany.bankapp.model ;  
  
public class Account {  
    ...  
}
```

- On the file system, sub-packages map onto sub-directories.
e.g. the Account class is stored in the corresponding sub-directory:

com/mycompany/bankapp/model/ Account.java

Implications for FXML

- In FXML, use a fully-qualified class name to refer to a class in a package:

```
fx:controller="com.mycompany.bankapp.controller.AccountController"
```

- In Java, use an absolute path to refer to an FXML file in a package:

```
new FXMLLoader(getClass().getResources("/com/mycompany/bankapp/view/account.fxml"));
```

ListView

ListView<X>

- A ListView<X> displays a list of items of type X.

- Items can be either:


- Strings
- Objects that have a `toString()` function

- Create a ListView in FXML:

```
<ListView fx:id="accountsLv"/>
```

- Create a ListView in Java:


```
ListView<Account> accountsLv = new ListView<Account>();
```



ListView Selection Models

- ListViews support two selection models:
 - SINGLE selection (the default model)
 - MULTIPLE selection
- In both selection models:
 - Clicking an item selects that item
 - The previously selected item is also deselected
- In the multiple selection model:
 - Shift-click or control-click to select multiple items
- If your application requires multiple selection:

```
listView.getSelectionModel().setSelectionMode(SelectionMode.MULTIPLE);
```



Setting a placeholder

- A placeholder node is shown when the ListView is empty.

- In FXML:

```
<ListView>
    <placeholder>
        <Label text="No accounts"/>
    </placeholder>
</ListView>
```

- In Java:

```
accountsLv.setPlaceholder(new Label("No accounts"));
```



Setting preferred dimensions

- In FXML:

```
<ListView prefWidth="300" prefHeight="200"/>
```

- In Java:

```
accountsLv.setPrefWidth( 300 );  
accountsLv.setPrefHeight( 200 );
```



Linking a ListView to the model

- **Goal:** Whenever the model changes the view is updated.

```
public class Customer {  
    private LinkedList<Account> accounts = new LinkedList<Account>();  
  
    public void addAccount(String type) {  
        accounts.add(new Account(type));  
    }  
}
```



We must notify the ListView that
a new Account was added to the list.


Linking a ListView to the model

- **Solution:** Use an ObservableList

```
public class Customer {  
    private ObservableList<Account> accounts = FXCollections.  
observableArrayList();  
  
    public void addAccount(String type) {  
        accounts.add(new Account(type));  
    }  
}
```

- Observers are notified whenever the list contents changes.

ObservableList “is a” relationships



Linking a ListView to the model

- Define the observable list as an immutable property with mutable state:

```
public class Customer {  
    private ObservableList<Account> accounts = ...;  
    public final ObservableList<Account> getAccounts() { return accounts;  
}  
}
```

- Bind the “items” property of ListView to the accounts property of customer
 - In FXML: <ListView items=”\${controller.customer.accounts}”/>
 - In Java: accountsLv.setItems(customer.getAccounts());

Selecting a ListView item

Selecting a ListView item

Goal: The user selects an item from a ListView then clicks a button to perform an action on the selected item.

Solution: Set the onAction handler for the button to perform the following two steps:

1. Get the selected item (pattern)
2. Perform an action on that item

ListView getter pattern

- A ListView has a getter that gets the currently selected item.
- It uses the `getSelectedItem()` method of the selection model.

```
public class CustomerController {  
    @FXML private ListView<Account> accountsLv;  
  
    private Account getSelectedAccount() {  
        return accountsLv.getSelectionModel().getSelectedItem();  
    }  
}
```

Example: View the selected account

FXML file:

```
<ListView fx:id="accountsLv"/>
<Button text="View Account" onAction="#handleViewAccount" />
```


Controller:

```
public class CustomerController {
    @FXML private ListView<Account> accountsLv;
    private Account getSelectedAccount() {
        return accountsLv.getSelectionModel().
getSelectedItem();
    }
    @FXML private void handleViewAccount(ActionEvent event) {
        Account account = getSelectedAccount();
        System.out.println("You selected: " + account);
    }
}
```

If `accountsLv` is clicked when no item is selected, `getSelectedAccount()` returns null.


Opening a window

Opening a window



Opening a window

- In MVC, each window requires 3 components:



- To open a new window:
 - Load the view from FXML (this in turn creates the controller)
 - Link the controller to the appropriate model
 - Create a new Stage, and show the view's scene graph on the stage

Opening a window

- UTS provides a package to help opening windows:

```
import au.uts.edu.ap.javafx.*;
```

- The ViewLoader class simplifies the process of showing a window:

```
ViewLoader.showStage(<model>, <FXML>, <title>, <stage>);
```

The model object

The FXML file

The window title

The stage



Source code for ViewLoader

```
package au.edu.uts.ap.javafx;
public class ViewLoader {
    public static <T> void showStage(T model, String fxml, String title, Stage stage)
        throws IOException {
        FXMLLoader loader = new FXMLLoader(Controller.class.getResource(fxml), null, null,
            type -> {
                try {
                    Controller<T> controller = (Controller<T>)type.newInstance();
                    controller.model = model;
                    controller.stage = stage;
                    return controller;
                } catch (Exception e) { throw new RuntimeException(e); }
            });
        Parent root = loader.load();
        stage.setTitle(title);
        stage.setScene(new Scene(root));
        stage.sizeToScene();
        stage.show();
    }
}
```

The model and stage are automatically “injected” into the controller.

ViewLoader examples

- Show a customer on the primary stage:

```
public class BankApplication extends Application {  
    @Override public void start(Stage stage) throws Exception {  
        Customer customer = new Customer("Mr Smith");  
        ViewLoader.showStage(customer, "/view/customer.fxml", "Customer",  
stage);  
    }  
}
```

- Show an account on a new stage (new window):

```
ViewLoader.showStage(account, "/view/account.fxml", "Account", new Stage());
```

Making controllers compatible with ViewLoader

- In the same helper package is an abstract Controller class:

```
package au.edu.uts.ap.javafx;

public abstract class Controller<X> {
    protected X model;
    protected Stage stage;
}
```

- If your controller extends this class, it will inherit the `model` and `stage` fields. `<X>` is the type of the model being used.
- `ViewLoader` will try to inject the model and stage into these fields.

Exposing a model property in the controller

- The old way...

```
public class CustomerController {  
    private Customer customer = new Customer("Mr Smith");  
    public final Customer getCustomer() { return customer; }  
}
```

- The new way...

```
public class CustomerController extends Controller<Customer> {  
    public final Customer getCustomer() { return model; }  
}
```

- The getter returns the model which is now an inherited field.

Example: CustomerController

```
public class CustomerController extends Controller<Customer> {  
    @FXML private ListView<Account> accountsLv;  
    public final Customer getCustomer() { return model; }  
    private Account getSelectedAccount() {  
        return accountsLv.getSelectionModel().getSelectedItem();  
    }  
    @FXML private void handleViewAccount(ActionEvent event) {  
        Account account = getSelectedAccount();  
        ViewLoader.showStage(account, "/view/account.fxml", "Account", new  
Stage());  
    }  
}
```

- Upon clicking the button, show /view/account.fxml and inject the selected account into the account controller.


Example: AccountController

```
public class AccountController extends Controller<Account> {  
    @FXML private TextField amountTf;  
    public final Account getAccount() { return model; }  
    private int getAmount() { return Integer.parseInt(amountTf.getText()); }  
    private void setAmount(int amount) { amountTf.setText(" " + amount); }  
    @FXML private void handleDeposit(ActionEvent event) {  
        getAccount().deposit(getAmount());  
        setAmount(0);  
    }  
    @FXML private void handleWithdraw(ActionEvent event) { ... }  
}
```

- The model field holds the selected account.
- Use getAccount() to access the account.

Closing a window

Closing a window




Closing a window

- Close a window with `stage.close()`.
- Every subclass of `Controller<X>` inherits a `stage` field.
Therefore, any method within a controller can call `stage.close()`.

```
public class AddAccountController extends Controller<Customer> {  
    @FXML private String typeTf;  
    public final Customer getCustomer() { return model; }  
    private String getType() { return typeTf.getText(); }  
    @FXML public void handleAdd(ActionEvent event) {  
        getCustomer().addAccount(getType());  
        stage.close();  
    }  
}
```


JavaFX controls

JavaFX controls



- JavaFX controls are nodes that tend to appear in forms.
- We have already seen:
 - Label
 - TextField
 - PasswordField
 - Button

More controls



- JavaFX also supports:

- CheckBox
- RadioButton
- ToggleButton
- ComboBox
- ChoiceBox
- Slider

CheckBox



- A CheckBox is either selected or not.
- **FXML:** <CheckBox text="Agree" fx:id="agreeCb"/>
- **Controller:** @FXML private CheckBox agreeCb;
- **CheckBox properties:**
 - selected: indicates whether the CheckBox is currently selected.
- e.g.

```
if (agreeCb.isSelected())
    System.out.println("User agrees");
```

RadioButton



- Related RadioButtons are placed in a ToggleGroup. Only one RadioButton in the group can be selected at a time.
- FXML:

```
<fx:define><ToggleGroup fx:id="genderTg"/></fx:define>
<RadioButton text="Male" userData="m" toggleGroup="$genderTg"/>
<RadioButton text="Female" userData="f" toggleGroup="$genderTg"/>
```
- Controller: @FXML private ToggleGroup genderTg;
- Properties of RadioButton
 - text: the text to display
 - userData: the raw data (e.g. to store in the model, or a database)
- Properties of ToggleGroup
 - selectedToggle: the RadioButton that is currently selected
- e.g. String s = genderTg.getSelectedToggle().getUserData().toString();
 System.out.println("The user selected: " + s);


ToggleButton



- Behaves the same way as a RadioButton.
- FXML:

```
<fx:define><ToggleGroup fx:id="musicTg"/></fx:define>
<ToggleButton text="On" userData="on" toggleGroup="$musicTg"/>
<ToggleButton text="Off" userData="off" toggleGroup="$musicTg"/>
```

ComboBox



Select an account ▾

- A ComboBox shows a popup list of items with a prompt.
- FXML:

```
<ComboBox fx:id="accountsCmb" promptText="Select an account"
           items="${controller.customer.accounts}" />
```
- Controller: `@FXML private ComboBox accountsCmb;`
- ComboBox properties are similar to ListView properties:
 - `items`: defines the list of items to display.
 - `selectionModel`: represents the selection state.
- e.g. `Account account = accountsCmb.getSelectionModel().getSelectedItem();`

ChoiceBox



- A ChoiceBox shows a popup list of items *without* a prompt.
- FXML: <ComboBox fx:id="accountsChb" items="\${controller.customer.accounts}" />
- Works the same way as a ComboBox.

Slider



- A Slider shows a thumb that can be slid on a track.
- FXML: <Slider min="1" max="5" showTickMarks="true" showTickLabels="true" majorTickUnit="1"/>

For more, see:

https://docs.oracle.com/javase/8/javafx/user-interface-tutorial/ui_controls.htm

Getter/Setter patterns for controls

- It is good practice to define getters and setters to wrap the controlled value. E.g.

```
private String getGender() {  
    return genderTg.getSelectedToggle().getUserData().toString();  
}  
  
private boolean isAgree() {  
    return agreeCb.isSelected();  
}  
  
private Account getAccount() {  
    return accountsCmb.getSelectionModel().getSelectedItem();  
}
```

Change listeners

Change listeners

- **Goal:** Be notified whenever an observable value changes.
- **Examples:**
 - Be notified when the text in a `TextField` changes.
 - Be notified when the selected item of a `ComboBox` changes.
 - Be notified when the selected toggle of a `ToggleGroup` changes.
- **Solution:** Register an observer that implements the `ChangeListener<X>` interface, where `<X>` is the type of value observed.

```
import javafx.beans.value.*;  
public interface ChangeListener<X> {  
    void changed(ObservableValue<? extends X> observable,  
                 X oldValue, X newValue);  
}
```

- Register the observer with `observable.addListener(observer)` ;

Any property can be observed for changes

- Print the account balance whenever it changes:

```
account.balanceProperty().addListener((obs, oldBal, newBal) ->  
    System.out.println("Balance changed from "+oldBal+" to "+newBal)  
);
```



- Print the text of a TextField whenever it changes:

```
nameTf.textProperty().addListener((obj, oldText, newText) ->  
    System.out.println("Text updated to " + newText)  
);
```

- Print the selected account whenever it is selected:

```
accountsLv.getSelectionModel().addListener((o, oldAcct, newAcct) -> {  
    if (newAcct != null) // if an account was selected  
        System.out.println("You selected " + newAcct);  
});
```

Example: Enable button when account is selected



Solution

- FXML:

```
<ListView fx:id="accountsLv" items="${controller.customer.accounts}"/>
<Button fx:id="viewAccountBtn" text="View Account" disable="true"
        onAction="#handleViewAccount"/>
```

- Controller:

```
@FXML private void initialize() {
    accountsLv.getSelectionModel().selectedItemProperty().addListener(
        observable, oldAccount, newAccount) ->
        viewAccountBtn.setDisable(getAccount() == null));
}
```

- This makes use of two properties:

- Register a ChangeListener to the **selectedItem** property of the selection model.
- When the selection changes, update the **disable** property of the Button.